

Supplier:	SolaLighting Limited, 23 Osier Way, Olney Office Park, Olney, MK46 5FP Tel: 01234 241466, Fax: 01234 241766 e-mail: daylight@solatube.co.uk Web: www.solatube.co.uk
Product:	Solatube 160 DS (250mm diameter) * or Solatube 290 DS (350mm diameter)*
Solatube Base Kit:	<ul style="list-style-type: none"> <li>• Impact-resistant and UV-stabilized polycarbonate roof dome with Raybender® 3000 fresnel lens system and LightTracker™ dome reflector, covered by 10-year warranty against loss of light transmission, excessive yellowing and loss of impact strength</li> <li>• Solatube roof flashing for specified roof type *</li> <li>• 99.7% reflective Spectralight® Infinity top tube assembly incorporating adjustable 0-30° angle section, pre-assembled dome ring and moisture control system</li> <li>• 99.7% reflective Spectralight® Infinity bottom tube assembly incorporating adjustable 0-30° angle section, pre-assembled ceiling ring with integrated triple seal and twist locking mechanism</li> <li>• Double-glazed diffuser, Vusion™ * or OptiView® * with white ceiling trim</li> <li>• Plus all seals, sealants, fixings and installation instructions</li> </ul>
Extension tube sections:	99.7% Spectralight® Infinity rigid tube extensions to cover roof to ceiling distance
Additional angle adaptors:	Additional 0-30° or 0-90° adjustable elbows are available if required.
Performance criteria:	Standard reference BRE test report No 212921: transmittance efficiency (T) should not be less than 0.35 mean measurement in overcast sky conditions or 0.45 in simulated direct sunlight at a solar altitude of 58.1 degrees (solar azimuth 180 degrees from north) as certified by the Building Research Establishment for a reference tube length of 2.7m.

\* specify as required



SolaLighting Limited, 23 Osier Way, Olney Office Park, Olney, MK46 5FP  
Tel 01234 241466 Fax 01234 241766  
Email: daylight@solatube.co.uk Website: www.solatube.co.uk